

SOUTHEASTERN

POWER PRODUCTS

SEP80 I-US

MODEL		SEP-80.0 KW
ENGINE	TIER 3	JOHN DEERE 4045HF285
CYLINDER		FOUR
CUBIC INCH		275
BORE / STROKE		4.19 X 5.00
ASPIRATION		TURBOCHARGE
H.P. @ 1800 RPM		115
NEWAGE / STANFORD		UCI 274C
OUTPUT VOLTS		208 THREE PHASE
OUTPUT AMPS		222.3
OUTPUT WATTS		80,000
FUEL @ 50 %		4.1 gph Approx
FUEL @ 100 %		7.2 gph Approx
LENGTH		68.0"
WIDTH		36.0"
HEIGHT		48.0"
WEIGHT		2475 Lbs

STANDARD FEATURES

12 Volt Electric Starter
12 Volt Battery Charging Alternator
Automatic Engine Shutdown Low Oil and High Coolant Temperature
Fuel Filter
Fuel Transfer Pump
Dry Air Cleaner
High Ambient Radiator
Single Bearing Generator
Brushless Excitor
Unit Mounted Solid State Voltage Regulator
Muffler Shipped Loose
Electronic Control Panel w/ Display for all Engine and Generator Functions
(not included)